



EMIT: A New Space Imaging Spectrometer Mission to Advance Modeling of the Earth System

Earth Surface Mineral Dust Source Investigation (EMIT)





(Photo: lanz/Flickr)

Robert O. Green, Natalie Mahowald and the EMIT Team

Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA



Jet Propulsion Laboratory Co Authors and EMIT Science **Team**




Team Member	Institution
Robert O. Green	JPL California Institute of Technology
Natalie Mahowald	Cornell University
David Thompson	JPL California Institute of Technology
Bethany Ehlmann	California Institute of Technology
Paul Ginoux	NOAA GFDL, Princeton University
Olga Kalashnikova	JPL California Institute of Technology
Ron Miller	NASA GISS, Columbia University
Greg Okin	University of California Los Angeles
Thomas Painter	JPL California Institute of Technology
Carlos Perez	Barcelona Supercomputing Center (formally NASA GISS)
Vincent Realmuto	JPL California Institute of Technology
Gregg Swayze	US Geological Survey
Roger Clark	Planetary Science Institute
Elizabeth Middleton	NASA GSFC
Luis Guanter	German Centre for Geosciences (GFZ)
Eyal Ben Dor	University of Tel Aviv



Mineral Dust Impacts Across the Earth System








Models are Used to Assess the Current my and Future Impacts of Mineral Dust








Dust in Earth System Models





And each mineral has different properties and interactions with Earth System

Iron oxides: Absorb SW, iron for ocean biogeochemistry

Kaolinite: Reflects SW, high pH

Feldspar: ice nuclei source

Clays, large particles: LW interactions

Scanza et al., 2015; 2018


In 3 aerosol size modes
(Zender et al., 2003; Mahowald et al., 2006; Liu et al., 2011)



Building dust into models



Using FAO soil datasets and "average" minerals in each soil type



Dust emissions

45

0

-45

-45

Scanza et al., 2015


In this implementation, including mineralogy details, the sign of radiative forcing switched from slightly cooling to slightly warming. An important difference.



Example: Current Mineral Dust Source Information



Current Soil Sample Locations



Concern: Using FAO soil data sets and "Average" soil properties from ≤5000 soils samples (mostly not in deserts) doesn't fully capture actual distribution and diversity.


New observations of arid land regions can help.

Journet et al., 2014



Imaging Spectroscopy Offers an Approach to Measure the Surface








Moon Mineralogy Mapper (M3): EARTH SUR Hydroxyl/Water Discovery










FAO Soil Map Compared to Airborne VSWIR Imaging Spectroscopy



Cuprite, Nevada Region

Soil Map

VSWIR Imaging Spectroscopy



Imaging spectroscopy provides a tested method for direct comprehensive measurement of surface mineral composition for the Earth's mineral dust source regions.




Key Minerals of Interest have Distinct Spectral Signatures





- Gypsum CaSO4.2H2O
- Calcite CaCO3
- --- Hematite Fe2O3
- Chlorite (Mg,Fe)3(Si,Al)4O10(OH)2-(Mg,Fe)3(OH)6

- —Kaolinite Al4[Si4O10[(OH)8
- —Goethite FeO.OH
- Dolomite CaMg(CO3)2
- ----Illite (K,H3O)(Al,Mg,Fe)2(Si,Al)4O10[(OH)2,(H2O)]
- ----Vermiculite (Mg,Fe+2,Al)3(Al,Si)4O10(OH)2*4H2O






EMIT Overview and Science Objectives

The source region composition for the Earth's mineral dust cycle is poorly known. Source knowledge is required to model the dust cycle and assess future scenarios. EMIT has two objectives.

1) Constrain the sign and magnitude of dust-related RF at regional and global scales. EMIT achieves this objective by acquiring, validating and delivering updates of surface mineralogy used to initialize ESMs.

2) Predict the increase or decrease of available dust sources under future climate scenarios. EMIT achieves this objective by initializing ESM forecast models with the mineralogy of soils exposed within at-





Mineral Dust and Radiative Forcing




Radiative forcing: The change in the Earth's energy balance as a function of an imposed perturbation

The optical characteristics of mineral dust influence the amount of energy absorbed or radiated.

Mineral composition is a key control of single-scattering albedo (SSA), the ratio of scattering extinction to total extinction.

- Hematite is a strong absorber (SSA < 1.0) in the VSWIR, contributing to positive forcing (warming)
- Clay minerals (illite, kaolinite, and montmorillonite) are strong scatters (SSA ≈ 1.0), contributing to negative forcing (cooling)




(modified from Sokolik and Toon, 1999)



Model Status



- Earth System Models are ready to accept more detailed Earth surface mineral dust source information.
- Earth System Models are being improved each year.



EMIT



(Photo: Todd Morris/Flickr)

Earth System Model




(Photo: lanz/Flickr)



EMIT uses Imaging Spectroscopy to Map Dust Source Region Minerals








Mineral Mapping Test in the Salton Sea, CA Dust Source Region





AVIRIS imaging spectroscopy measurements of the Salton Sea region in Southern California acquired as part of the 2014 NASA HyspIRI airborne campaign.

Hematite



Goethtite **Carbonates Clay Minerals** Illite



Validating the Mineral California Institute of Technology Spectroscopy at Salton Sea, CA










Existing FAO Mineralogy versus Imaging Spectroscopy








Comparison





EMIT Target Areas are focused in the Arid Land Regions








ISS is Ideal for EMIT: ELC 1 Site 8, Nadir View







EMIT Instrument: F/1.8 VSWIR Dyson Imaging Spectrometer




Instrument Overview

EMIT is a Class C implementation of a mature F/1.8 VSWIR-Dyson Spectrometer that leverages NASA Research and Technology investments, including the ESTO IIP SWIS Dyson spectrometer.

Prototype Spectrometer



Test Spectra




EMIT measurement


Spectral: 380-2510 nm
Radiometric: ≥100 SNR in retrieval wavelengths, without saturation over bright land
Spatial: ~30 m sampling

VSWIR Detector 1280 x 480
























The EMIT Instrument Draws from a Long **History of Imaging Spectrometer Development**





1982

- First Imaging Spectrometer AIS proposed in 1979 first flights in 1982
- AVIRIS imaging spectrometer > 1000 refereed journal articles
- NIMS imaging spectrometer to Jupiter 1989
 - VIMS imaging spectrometer to Saturn



MICAS Miniature Integrated Camera and Imaging Spectrometer to Comet



Enabling partner in Hyperion-Earth, CRISM-Mars and ARTEMIS-Earth imaging spectrometers (gratings, designs, calibration, science)

Proposed and Developed NASA Moon Mineralogy Mapper (M3)



24 Months

> 7 Airborne/Rover-type Imaging Spectrometer operating at cryogenic

temperature and in a vacuum (2005-2015) < 18 Months_{AVIRIS-NG 2012} PRISM 2012




2009

24 Months 24 Months













EMIT-2018



Summary and Conclusions



- The mineral dust cycle impacts many elements of the Earth system.
- To understand these impacts and predict how they may change in future climate scenarios the dust cycle must be modeled.
- A current challenge is poor constraint of the surface mineral composition for the dust source regions of the Earth.
- The VSWIR imaging spectroscopy of EMIT provides a direct and well established method to measure surface mineralogy.
- Initialization of ESMs with EMIT measurements will reduce uncertainty in modeled radiative forcing and allow more accurate investigation of future scenarios.
- EMIT measurements and products will be delivered to the designated NASA DAAC and made available to support a range of scientific research.
- EMIT is scheduled to launch in 2021 and proceed to address its objectives.



Thank you

